



## BRIDGE FAUCET

### INSTALLATION INSTRUCTIONS

Before installing, read entire Bridge Faucet Installation Instructions. Observe all local building and safety codes.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-866-855-2284. If you need assistance or have questions while installing your Bridge Faucet, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures and plumbing. Signature Hardware accepts no liability for any damages to the floor, walls, plumbing or for personal injury during installation.

Shut off the water supply lines at the sink where the new faucet is being installed.

### TOOLS AND MATERIALS:

Adjustable Wrench

Teflon Pipe Tape

Basin Wrench

### INSTALLATION

1. Remove the lock nuts from the bottom of the faucet and insert the faucet through the mounting holes.
2. Hand-tighten washers (if included) and hex nuts to secure.
3. Check to make sure the faucet is properly aligned and adjust as needed. When the faucet is in the proper position, finish tightening the hex nuts with your adjustable wrench.
4. Hand tighten to attach the hot and cold water feed tubes to the water inlets; hot water is always on the left and cold water is always on the right. Give a ¼ turn with pliers or wrench, but don't over tighten. Curve tubes as necessary to ensure there are no kinks or knots.

**Tip:** Place plumber's tape on hoses and pipes before you attach supply lines to ensure leak-free connections.

5. After all connections have been made, turn on the water supply, check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the faucet on and allow the water to flow through the spout for approximately 60 seconds.