



FLUSH LEVER

INSTALLATION INSTRUCTIONS

Before installing, read entire Flush Lever Installation Instructions. Observe all local building and safety codes.

For the following installation instructions for your new flush lever it is assumed that any old fixtures have been removed and any repairs or modifications have been completed.

Unpack and inspect the product for any shipping damages. If you find damages, do not install. Contact Customer Service at 1-866-855-2284. If you need assistance or have questions while installing your flush lever, contact Customer Service.

We recommend consulting a professional if you are unfamiliar with installing bathroom fixtures. Signature Hardware accepts no liability for any damage to the floor, walls, plumbing or for personal injury during installation.

TOOLS AND MATERIALS:

Pliers

INSTALLATION

1. Remove the toilet tank lid.
2. If assembled, unscrew the washer, locknut and flush arm from the back of the new flush lever.

Note: Washers and locknuts are left-hand threaded. Turn clockwise to loosen and counter-clockwise to tighten.

3. Insert the lever stem through the handle hole on the toilet tank.
4. Secure the lever assembly with the rubber washer and locknut.

Tip: Be careful not to overtighten the locknut, doing so will prevent the lever from moving freely. If you are having trouble turning your new lever, slightly loosen the locknut until it moves evenly.

5. Attach the flapper chain to the flush arm on the lever body. Adjust the chain length as needed.
6. Test the lever to verify that all parts operate smoothly.
7. Finish your installation by replacing your toilet tank lid.